

# SPH 3000~6000TL BL-UP

- Smart load management via dry contact
- UPS function, 10ms transition
- Scalable system configuration
- VPP interface ready
- Remote smart O&M
- 2 DC/AC Ratio



P O W E R  
- I N G O  
T O M O -  
R R O W O

**GROWATT**

[www.ginverter.com](http://www.ginverter.com)

Datasheet	SPH3000TL BL-UP	SPH3600TL BL-UP	SPH4000TL BL-UP	SPH4600TL BL-UP	SPH5000TL BL-UP	SPH6000TL BL-UP
<b>Input data(PV)</b>						
Max. recommended PV power (for module STC)	6500W	7500W	8500W	9000W	9500W	10600W
Max. DC voltage	550V					
Start voltage	120V					
MPP voltage range/ Nominal Voltage	120-550V/370V					
No. of MPP trackers	2					
No. of PV strings per MPP tracker	1					
Max. input current per MPP tracker	13.5A					
Max. short-circuit current per MPP tracker	16.9A					
<b>Output data(AC)</b>						
AC nominal power	3000W	3680W	4000W	4600W	5000W	6000W
Rated AC apparent power	3000VA	3600VA	4000VA	4600VA	5000VA	6000VA
Nominal AC voltage (range)	230V/ (180Vac-260Vac)					
AC grid frequency (range)	50Hz/60Hz (45Hz-55Hz/55Hz-65Hz)					
Rated, output current	13.5A	16A	17.5A	20A	22A	27A
Adjustable power factor	0.8leading...0.8lagging					
THDi	<3%					
AC grid connection type	Single phase					
<b>Battery data (DC)</b>						
Battery voltage range	42~59V					
Max charging and discharging current	66A	75A	85A	85A	85A	85A
Continuous charging and discharging power	3000W	3680W	4000W	4000W	4000W	4000W
Type of battery	Lithium /Lead-acid					
<b>Backup power(AC)</b>						
Max. AC output power	3000W	3680W	4000W	4000W	4000W	4000W
Rated output current	13A	16A	17.5A	17.5A	17.5A	17.5A
Nominal AC output voltage	230Vac					
Nominal AC output frequency	50/60HZ					
THDv	<3%					
Switch time	<10ms					
<b>Efficiency</b>						
MAX. efficiency	97.20%	97.20%	97.30%	97.40%	97.50%	97.60%
European efficiency	97%	97%	97.10%	97.10%	97.20%	97.20%
MPPT efficiency	≥99.5%					
<b>Protection devices</b>						
DC switch	Yes					
DC reverse polarity protection	Yes					
AC/DC surge protection	Yes					
Battery reverse protection	Yes					
AC short-circuit protection	Yes					
Ground fault monitoring	Yes					
Grid monitoring	Yes					
Anti-islanding protection	Yes					
Residual-current monitoring unit	Yes					
Insulation resistance monitoring	Yes					
<b>General data</b>						
Dimensions (W / H / D)	565/456/188mm					
Weight	27kg					
Operating temperature range	-25°C ... +60°C					
Nighttime power consumption	< 10 W					
Topology	Transformerless					
Cooling	Natural					
Protection degree	IP65					
Relative humidity	0~100%					
Altitude	2000m					
PV DC Connection	H4/MC4(Optional)					
Battery DC Connection	OT Terminal					
AC connection	Connector					
Display	LCD+LED					
Interfaces:RS485/CAN/USB	Yes					
Monitor : RF/WIFI/GPRS	Optional					
Warranty: 5 years / 10 years	Yes/Optional					

CE, IEC62109, G98/G99, VDE0126-1-1, AS4777, CEI 0-21, VDE-AR-N4105, IEC C 15-712, EN50549, IEC 61727, IEC 62116, IEC 62040, C10/11, NRS 097-2-1

\* The AC voltage range and frequency range may vary depending on specific country grid standard.  
All specifications are subject to change without notice.